

GL Specialized Inks (Pty) Ltd

Material Safety Data Sheet

Conforms to EU Directive 91/155/EEC and ISO 11014-1

Product name : UV Screen F/G Inks

Version : 1.00 Date of issue : 12/17/2012.

Date of previous issue : No previous validation.

1. Identification of the substance/preparation and of the company

Product name : UV Screen F/G Inks

Product code : 350

 Use of the substance/mixture
 : Ultraviolet curable FG ink

 Supplier
 : GL Specialized Inks (Pty) Ltd

8 Hawthorne Place, Mahogany Ridge, Pinetown, Durban

Emergency telephone number : Office Hours:

031 - 700 6455 After hours:

082 451 6588 (Jay) 082 780 8875 (Julie) 082 452 2143 (Gordon)

2. Composition/information on ingredients

Chemical characterization : Mixture.

Ingredient name	CAS number	%	EC number	Classification
acrylate mixture Pigment mixture Photoinitiator titanium dioxide Calcium carbonate silica, amorphous, fumed carbon black See Section 16 for the full text of the R-phrases declared above.	13463-67-7 471-34-1 7631-86-9 1333-86-4	50 - 70 0 - 9 4 - 12 0 - 29 10 - 15 1 - 5 0 - 4	236-675-5 207-439-9 231-545-4 215-609-9	Not classified Not classified. Xi; R36/38 Not classified. Not classified.

Occupational exposure limits, if available, are listed in Section 8.

This MSDS covers all formulations in the range. Not all of the components listed will be present in an individual formulation. Formula specific MSDS available on request.

All inks are formulated in accordance with Nestle - Guidance note on packaging inks, dated 22/4/2010 and subsequent versions. It is the responsibility of the converter to test for migration before the first application, and ensure that the inks comply with the migration specific limits.

3. Hazards identification

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Not classified.

Physical/chemical hazards: No known significant effects or critical hazards.Human health hazards: No known significant effects or critical hazards.Environmental hazards: No known significant effects or critical hazards.

See Section 11 for more detailed information on health effects and symptoms.

4. First aid measures

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if symptoms occur.

Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at rest in a position

comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to

do so by medical personnel. Get medical attention if symptoms occur.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes.

Get medical attention if symptoms occur.

:

Product name : UV Screen F/G Inks

Version : 1.00 Date of issue : 12/17/2012.

Date of previous issue: No previous validation.

Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

See Section 11 for more detailed information on health effects and symptoms.

5. Fire-fighting measures

Extinguishing media

Suitable : In case of fire, use water spray (fog), foam or dry chemical.

Not suitable : None known.

Special exposure hazards : No specific hazard.

Hazardous thermal decomposition

products

Decomposition products may include the following materials: carbon oxides (CO, CO₂).

Some metallic oxides.

Special protective equipment for fire-

fighters Remark : Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: Fine powder forms flammable and explosive mixtures in air. (carbon black)

6. Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate

surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment

(see Section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and

sewers. Inform the relevant authorities if the product has caused environmental pollution

(sewers, waterways, soil or air).

Methods for cleaning up : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water

courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling : Wash thoroughly after handling.

Storage : Keep container tightly closed. Keep container in a cool, well-ventilated area.

Packaging materials

Recommended : Use original container.

8. Exposure controls/personal protection

Exposure limit values

<u>Ingredient name</u> <u>Occupational exposure limits</u>

titanium dioxide ACGIH (United States).
TWA: 10 mg/m³

ACGIH TLV (United States, 1/2004). Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. 1996 Adoption Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR

58(124) :36338-33351, June 30, 1993, for revised OSHA PEL. Refers to

Appendix A -- Carcinogens.

TWA: 10 mg/m³ 8 hour(s). Form: All forms

calcium carbonate. ACGIH TLV (United States, 1/2004). Notes: The value is for total dust

containing no asbestos and < 1% crystalline silica.

TWA: 10 mg/m³ 8 hour(s). Form: All forms

ACGIH (United States).

TWA: 10 mg/m³ TWA: 6 mg/m³

carbon black ACGIH TLV (United States, 1/2004). Notes: Substance identified by other

sources as a suspected or confirmed human carcinogen. 1996 Adoption

Refers to Appendix A -- Carcinogens.

TWA: 3.5 mg/m³ 8 hour(s). Form: All forms

Respiratory protection

silica, amorphous, fumed

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

:

Product name : UV Screen F/G Inks

Version : 1.00 Date of issue : 12/17/2012.

Date of previous issue: No previous validation.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn

at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommended:

Neoprene gloves. Nitrile gloves.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or

dusts.

Skin protection : Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before handling this

product.

9. Physical and chemical properties

General information

Appearance

Physical state : Liquid. (Viscous liquid.)

Color : Various

Odor : Sweetish. (Slight.)

Important health, safety and environmental information

Boiling point : $>150^{\circ}$ C (302°F)

Flash point : Closed cup: >95°C (203°F). (Pensky-Martens.)

Flammability (solid, gas) : Combustible liquid

Explosive properties : Slightly explosive in the presence of the following materials or conditions: open flames,

sparks and static discharge and heat.

Relative density : 0.95 to 1.25 g/cm³

Solubility : Insoluble in the following materials: cold water, hot water, methanol, diethyl ether, n-octanol

and acetone.

10. Stability and reactivity

Stability : The product is stable.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Materials to avoid : Highly reactive or incompatible with the following materials: oxidizing materials.

Reactive or incompatible with the following materials: acids.

Hazardous decomposition products : Evolves toxic fumes when heated to decomposition.

11. Toxicological information

Potential acute health effects

Inhalation: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Skin contact: Slightly irritating to the skin.Eye contact: Slightly irritating to the eyes.

Acute toxicity

Product/ingredient name Result **Species** Dose **Exposure** 6450 mg/kg Calcium Carbonate LD50 Oral Rat **TDLo Oral** Rat 60 gm/kg silica, amorphous, fumed LD50 Oral 3160 mg/kg Rat carbon black LD50 Dermal Rabbit >3 g/kg LD50 Oral >15400 mg/kg Rat

Potential chronic health effects

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation : Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or

asphyxiation.

Ingestion : Ingestion may cause nausea, weakness and central nervous system effects.

Skin : Repeated skin exposure can produce local skin destruction or dermatitis.

Target organs : Contains material which causes damage to the following organs: lungs, upper respiratory

tract, skin, eye, lens or cornea.

Product name : UV Screen F/G Inks

Version : 1.00 Date of issue : 12/17/2012.

Date of previous issue: No previous validation.

12. Ecological information

Ecotoxicity data

Ingredient nameSpeciesPeriodResulttitanium dioxideDaphnia magna (EC50)48 hour(s)>1000 mg/l

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Methods of disposal : Non-hazardous waste

Waste must be disposed to a landfill permited in terms of the Department of Water Affairs and Forestry's minimum requirements for waste disposal to landfill, and the minimum

requirements for the handling, classification and disposal of hazardous waste.

14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
ADR / SANS 10228 Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-

15. Regulatory information

SANS 10265 / EU Regulations

Risk phrases : This product is not classified according to EU legislation.

Product use : Classification and labeling have been determined according to EU Directives 67/548/EEC

and 1999/45/EC (including amendments) and take into account the intended product use.

- Industrial applications.

16. Other information

Full text of R-phrases referred to in

sections 2 and 3 - Europe

: R36/38- Irritating to eyes and skin.

Prepared by : GL Inks EHS

Notice to reader

This MSDS summarises at the date of issue our best knowledge of the health, safety and environmental hazard information related to the product and, in particular, how to safely handle, use, and transport the product in the workplace. Since GL Specialized inks (Pty) Ltd cannot anticipate or control the conditions under which the product may be handled, used, stored or transported, each user must, prior to usage, review the MSDS in the context of how the user intends to handle, use, store or transport the product in the workplace and beyond; and communicate such information to all relevant parties. If clarification, or further information is required to ensure that an appropriate assessment can be made, the user should contact the company.

We shall not assume any liability of the accuracy or completeness of the information contained herein, or any advice given, unless there has been gross negligence on our part. In such an event, our liability shall be limited to the value of the product purchased from GL. Our responsibility for the product as sold is subject to our standard terms and conditions. All risk with possession and application of the product passes on delivery.