

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 3900 Series Flexible Vinyl Banner Screen Ink
Product code : 494
Synonyms : This SDS covers all formulations in the range. Not all components will be present in an individual formulation. Formulae specific SDS available on request.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : PRINTING INK

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

GL Specialized Inks (Pty) Ltd
8 Hawthorne Place
Mahogany Ridge
Westmead
Durban
Telephone: +27 (0)31 700 6455
Fax: +27 (0)31 700 6187

After hours:
082 451 6588 (Jay)
082 780 8837 (Julie)

www.gl-inks.com
jay@gl-inks.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Repeated exposure, Category 1	H372
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

3900 Series Flexible Vinyl Banner Screen Ink

Safety Data Sheet

In accordance with SANS 10234:2008

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

2-phenoxyethyl acrylate; 1-vinylhexahydro-2H-azepin-2-one; hexamethylene diacrylate, hexane-1,6-diol diacrylate; 2-HYDROXY-2-METHYLPROPIOPHENONE 70-90%; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one

Hazard statements (CLP) :

H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H361 - Suspected of damaging fertility or the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P260 - Do not breathe fume, mist, spray, vapours
P273 - Avoid release to the environment
P280 - Wear eye protection, protective clothing, protective gloves
P301+P312 - IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P314 - Get medical advice/attention if you feel unwell
P501 - Dispose of contents to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cl 77891 substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (AT, BE, BG, DE, DK, ES, FR, GB, GR, IE, LT, LV, NL, PT, SE, SK)	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-no) 01-2119489379-17	< 60	Not classified
Bronze Powder substance with national workplace exposure limit(s) (SK)	(CAS-No.) 7440-66-6 (EC-No.) 231-175-3 (REACH-no) 01-2119467174-37-XXXX	< 40	Not classified
2-phenoxyethyl acrylate	(CAS-No.) 48145-04-6 (EC-No.) 256-360-6 (REACH-no) 01-2119980532-35-XXXX	1 - 40	Skin Sens. 1, H317 Aquatic Chronic 2, H411
hexamethylene diacrylate, hexane-1,6-diol diacrylate	(CAS-No.) 13048-33-4 (EC-No.) 235-921-9 (EC Index-No.) 607-109-00-8	1 - 40	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317
Calcium carbonate substance with national workplace exposure limit(s) (FR, LV, PL)	(CAS-No.) 471-34-1 (EC-No.) 207-439-9 (REACH-no) 01-2119486795-18	< 20	Not classified
1-vinylhexahydro-2H-azepin-2-one	(CAS-No.) 2235-00-9 (EC-No.) 218-787-6 (REACH-no) 01-2119977109-27	1 - 20	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 1, H372
aluminium powder (stabilised) substance with national workplace exposure limit(s) (AT, BE, BG, DE, DK, ES, FR, GB, HU, IE, LV, PT, SE, SK)	(CAS-No.) 7429-90-5 (EC-No.) 231-072-3;231-072-3b (EC Index-No.) 013-002-00-1 (REACH-no) 01-2119529243-45-XXXX	< 20	Not classified

3900 Series Flexible Vinyl Banner Screen Ink

Safety Data Sheet

In accordance with SANS 10234:2008

Triethanolamine	(CAS-No.) 102-71-6 (EC-No.) 203-049-8 (REACH-no) 01-2119486482-31	1 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Carbon Black substance with national workplace exposure limit(s) (BE, DK, ES, FI, FR, GB, GR, IE, PT, SE)	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	< 10	Not classified
SILICA substance with national workplace exposure limit(s) (DE, LV)	(CAS-No.) 7631-86-9 (EC-No.) 231-545-4 (REACH-no) 01-2119379499-16	1 - 10	Not classified
CELLULOSE ACETATE BUTYRATE	(CAS-No.) 9004-36-8	1 - 10	Acute Tox. 4 (Dermal), H312
2-HYDROXY-2-METHYLPROPIOPHENONE 70-90%	(CAS-No.) 7473-98-5 (EC-No.) 231-272-0	< 10	Acute Tox. 4 (Oral), H302 Aquatic Chronic 3, H412
diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide	(CAS-No.) 75980-60-8 (EC-No.) 278-355-8 (EC Index-No.) 015-203-00-X	< 10	Repr. 2, H361f
2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one	(CAS-No.) 71868-10-5 (EC-No.) 400-600-6 (EC Index-No.) 606-041-00-6	1 - 10	Acute Tox. 4 (Oral), H302 Aquatic Chronic 2, H411
2-benzyl-2-dimethylamino-4-morpholinobutyrophenone	(CAS-No.) 119313-12-1 (EC-No.) 404-360-3 (EC Index-No.) 606-047-00-9	1 - 10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe fume, mist, spray, vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

3900 Series Flexible Vinyl Banner Screen Ink

Safety Data Sheet

In accordance with SANS 10234:2008

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe fume, mist, spray, vapours. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.
--------------------	---

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon Black (1333-86-4)		
United Kingdom	Local name	Carbon black
United Kingdom	WEL TWA (mg/m ³)	3,5 mg/m ³
United Kingdom	WEL STEL (mg/m ³)	7 mg/m ³
CI 77891 (13463-67-7)		
EU	Local name	Titanium dioxide
EU	Notes	SCOEL Recommendations (Ongoing)
United Kingdom	Local name	Titanium dioxide
United Kingdom	WEL TWA (mg/m ³)	4 mg/m ³ respirable 10 mg/m ³ total inhalable
aluminium powder (stabilised) (7429-90-5)		
United Kingdom	Local name	Aluminium
United Kingdom	WEL TWA (mg/m ³)	2 mg/m ³ alkyl compounds 2 mg/m ³ salts, soluble 10 mg/m ³ metal, inhalable dust 4 mg/m ³ metal, respirable dust

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Avoid all unnecessary exposure. Safety glasses. Gloves. Protective clothing.

Materials for protective clothing:

Wear suitable protective clothing

Hand protection:

In case of repeated or prolonged contact wear gloves

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

3900 Series Flexible Vinyl Banner Screen Ink

Safety Data Sheet

In accordance with SANS 10234:2008



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: Sweet.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 150 °C
Flash point	: > 95 °C
Auto-ignition temperature	: 485 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 13 vol %
Upper explosive limit (UEL)	: 10 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Oral: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified

3900 Series Flexible Vinyl Banner Screen Ink

Safety Data Sheet

In accordance with SANS 10234:2008

Acute toxicity (inhalation) : Not classified

ATE CLP (oral)	2000 mg/kg bodyweight
----------------	-----------------------

Triethanolamine (102-71-6)

LD50 oral	8000 mg/kg bodyweight
LD50 dermal	> 10000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 1,8 mg/l

CI 77891 (13463-67-7)

LD50 oral	> 5000 mg/kg bodyweight
LD50 dermal	> 10000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 6820 mg/l

Calcium carbonate (471-34-1)

LD50 oral	> 2000 mg/kg bodyweight
LD50 dermal	> 2000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 3000 mg/l

SILICA (7631-86-9)

LD50 oral	> 5000 mg/kg bodyweight
LD50 dermal	> 2000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 2080 mg/l

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Acute aquatic toxicity : Not classified
Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Triethanolamine (102-71-6)

LC50 fish 1	11800 mg/l
EC50 other aquatic organisms 1	2038 mg/l waterflea
EC50 other aquatic organisms 2	216 mg/l

CI 77891 (13463-67-7)

LC50 fish 1	> 10000 mg/l
EC50 other aquatic organisms 1	> 10000 mg/l waterflea
EC50 other aquatic organisms 2	> 10000 mg/l

Calcium carbonate (471-34-1)

LC50 fish 1	> 100 mg/l
EC50 other aquatic organisms 1	> 100 mg/l waterflea

SILICA (7631-86-9)

LC50 fish 1	> 10000 mg/l
EC50 other aquatic organisms 1	> 10000 mg/l waterflea

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

3900 Series Flexible Vinyl Banner Screen Ink

Safety Data Sheet

In accordance with SANS 10234:2008

Triethanolamine (102-71-6)	
Log Pow	-1,6
Calcium carbonate (471-34-1)	
Log Pow	-2,12
SILICA (7631-86-9)	
Log Pow	0,53

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
3082	3082	3082	3082	3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate)	Environmentally hazardous substance, liquid, n.o.s. (2-phenoxyethyl acrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate), 9, III, (E)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (2-phenoxyethyl acrylate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : M6
Special provisions (ADR) : 274, 335, 601, 375
Limited quantities (ADR) : 5l
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Mixed packing provisions (ADR) : MP19

3900 Series Flexible Vinyl Banner Screen Ink

Safety Data Sheet

In accordance with SANS 10234:2008

Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:



Tunnel restriction code (ADR)	: E
-------------------------------	-----

- Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP2, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

- Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197
ERG code (IATA)	: 9L

- Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

- Rail transport

Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19

3900 Series Flexible Vinyl Banner Screen Ink

Safety Data Sheet

In accordance with SANS 10234:2008

Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Triethanolamine - hexamethylene diacrylate, hexane-1,6-diol diacrylate - 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	3900 Series Flexible Vinyl Banner Screen Ink - Triethanolamine - 2-phenoxyethyl acrylate - hexamethylene diacrylate, hexane-1,6-diol diacrylate - 2-HYDROXY-2-METHYLPROPIOPHENONE 70-90% - 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	3900 Series Flexible Vinyl Banner Screen Ink - 2-phenoxyethyl acrylate - 2-HYDROXY-2-METHYLPROPIOPHENONE 70-90% - 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	aluminium powder (stabilised)

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide is listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

3900 Series Flexible Vinyl Banner Screen Ink

Safety Data Sheet

In accordance with SANS 10234:2008

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H361	Suspected of damaging fertility or the unborn child
H361f	Suspected of damaging fertility
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product